



ESD UniClean®

Neutral cleaner especially for ESD-equipment for all kinds of working tables, shelves and other equipment

Part No. 090606-6 // Content: 6 l Combi Container

CLEANING TECHNOLOGY

Made in Germany



Application overview

The detergent can be used as ready-to-use liquid or blended with water in a 1:10 ratio. Simply spray onto the surface or apply with a cloth and wipe it clean while it is still wet. Not suitable for acrylic glass.

Technical data	
Color	blue
Odor	lemon
ph-value at 20°C	7
Melting point	not determined
Initial boiling point and range	not determined
Flash point	not determined
Flammability (solid & gas)	not applicable
Explosion limits	not determined
Ignition temperature	425° C
Density at 25° C	0,979 g / cm ³
Water solubility	easily soluble
Viscosity (dyn.) at 20° C	21 mPa s
Application	pure or up to 1:10 with water
Storing frost-free	in original container
Hazards identification	Not classified as hazardous
ESD UniClean® has antistatic properties and is dust repellant. The electrostatic charge on screens will be suppressed.	

Applications	
Solder paste	—
Colophonium flux	
Waterbased flux	—
Solder paste (soldered)	—
Working tables / Shelves	++
Screens / Equipment	++
Oil / Grease	++
Spray-in-air systems	—
Spray-in-immersion systems	—
Air-in-immersion systems	—
Ultrasonic systems	—
Manual application	++
++ = ideal for application, + = recommended, o = optionally applicable, — = not recommended	
Note: The spreadsheet only shows a general overview of the product specifications.	
Cleaning tests are reasonable to determine the optimum cleaner configuration. Such tests may be carried out directly at the kolb demonstration center in Willich / Germany or Shanghai / China or can be initiated by contacting your local kolb partner.	