



Technical information

WaterStabilizer

Preservative (Additive)











Technical Data

Applications

Process

		Additive LeadFree SaltFree Compliant Compliant		
Density at 20°C	1,021 g/cm ³	Water based pH-neutrale stabilizer Extends the life span of the rinse water by 5 to 10 times and it has been developed to preserve the rinse water		
Viscosity at 20°C	23,0 mPas			
ph-value at 20°C	7,0 at 30g/l			
Boiling temperature	100° C			
Explosion risk	none			
Solubility in water	unlimited	Reaches its best efficiency at a mixing ratio of 30ml to 10l rinse water		
Application temperature	20 - 45°C			
Application	diluted 30ml at 10l			
Storing frost-free	in original container			
Waste key	07 06 99			
WPC	1			
Preserving:				
Rinsing water	++*	Please be aware: The product may irritate mucuous membrane, skin and eyes!		
		For commercial use only!		
		-		
		Your WaterStabilizer supplier:		
		-		
		-		
	PowerSpray systems			
PS AF	AirFlow systems	Part No. 090602 // PU: 2 x 5 l		
PowerSpray® AirFlow®		Part No.		
Made in Germany		Part No.		

*++ = ideal for application, + = recommended, o = usable but not recommended, - = not recommended Note: The spreadsheet only shows a general overview of the cleaning media specifications. Rinsing with tap water with a too high lime conncentration may cause lime residues after drying. Cleaning tests are reasonable and necessary to determine the optimum cleaner or additive configuration. Such tests may be carried out directly at the kolb Demonstration Center in Willich / Germany or can be initiated by contacting one of our international subsidiaries.

Kolb Cleaning Technology GmbH	Phone	+49 (0) 2154 9479 - 38
Karl-Arnold-Str. 12 · D - 47877 Willich	Fax	+49 (0) 2154 9479 - 47
Further information: www.kolb-ct.com	e-mail	info@kolb-ct.com