



WipeEx® SA120

Aqueous pH-neutral ready to use detergent for the machine cleaning with fleece for underscreen cleaning in screen printers

Part No. 090616-2 // Content: 2 x 5 l

CLEANING TECHNOLOGY

Made in Germany



Application overview

The cleaner is ready for use, can be used both directly in the cleaning tank of screen printers, as well as for the manual cleaning of screens and stencils.

Technical data	
Color	transparent
Odor	specific
pH-value	not measurable
Initial boiling point and range	not determined
Flash point	88 °C
Ignition temperature	205 °C
Density at 20 °C	0,92 g / cm ³
Water solubility	1,9 g / l
Viscosity at 20 °C	11,4 mm ² / s
Application	pure
Application temperature	20 - 45 °C
Storing frost-free	in original container
EWC key number	070604
CLP / GHS	Not classified as hazardous
<p>WipeEx® SA 120 cleans quickly, thoroughly and with best possible material protection SMD adhesive and SMD paste of technical screens, stencils, PumpPrints.</p>	

Applications	
SMD adhesive	++
Solder paste	++
Low voc flux	—
Colophonium flux	—
Waterbased flux	—
Solder paste (soldered)	—
Stainless steel / Glas	—
Spray-in-air systems	—
Spray-in-immersion systems	—
Air-in-immersion systems	—
Screen printer / cleaning unit	++
Manual application	++
<p>++ = ideal for application, + = recommended, o = optionally applicable, — = not recommended</p> <p>Note: The spreadsheet only shows a general overview of the product specifications.</p> <p>Cleaning tests are reasonable to determine the optimum cleaner configuration. Such tests may be carried out directly at the kolb demonstration center in Willich / Germany or Shanghai / China or can be initiated by contacting your local kolb partner.</p>	